

# **Centurion<sup>™</sup> C3-A**

Three Cylinder Fully Automatic Gas Cabinet with 1 x 1 x 1 Enclosure



**SEMI-GAS®** supplies SEMI S2 certified, production-ready ultra high purity gas source systems, distribution systems and control technology to leaders in the Semiconductor industry and related high-tech fields. Built to address the most rigorous precision and purity demands of these specialized applications, SEMI-GAS® solutions are globally renowned for their premier levels of safety, quality, and performance.

### **DESIGN STANDARDS**

- ♦ Conforms to SEMI S2 Standards
- UL Labeled
- Conforms to Uniform Building and Fire Codes
- Upholds Sample Validation Testing Standards
- Helium Leak Tested to 1x10<sup>-9</sup> atm-cm<sup>3</sup>/sec
- ♦ Equipped with GigaGuard<sup>™</sup> PLC Controller

### FEATURES

- Safely Dispenses Hazardous Process Gases
- Separate Enclosures for Individual Cylinders
- Performs Purging Automatically
- Performs Cylinder Switchover Automatically
- Includes Ergonomically Positioned Color Touch Screen
- Intuitive Operating Interface and Control
- Continuously Monitors System Conditions for Alarms
- Maintains Detailed Alarm Logs
- Multiple Communications Protocols Available
- Optional Z-Purge
- Optional 1CE200 Enclosures Specifically Designed for Silane Delivery

### **ENGINEERING DATA**

- Dimensions: 86" T X 45.75" W X 23" D
- ◆ Exhaust Duct- 1CE200: 8" Diameter
- Exhaust Duct- 1CE: 6" Diameter
- Window Open Duct Flow- 1CE200: 850 SCFM
- Window Open Duct Flow- 1CE: 350 SCFM
- Voltage: 110 to 240 VAC, 1 Phase
- Frequency: 50 to 60 Hz

### MATERIALS OF CONSTRUCTION

- ♦ Welded 11 Ga Steel Enclosure
- Self-Closing and Self-Latching Door
- ♦ Self-Closing and Self-Latching Window
- ◆ Heavy Cast Aluminum Cylinder Brackets
- Polycarbonate Face Shield
- Durable, Corrosion Proof, Non-Skid Floor Mat
- UL Approved Fire Sprinkler
- ♦ 1/4" Thick Safety Glass Window



### ORDERING INFORMATION

Contact your SEMI-GAS<sup>®</sup> sales rep or visit www.semi-gas.com

**BY APPLIED ENERGY SYSTEMS** 

180 Quaker Lane Malvern, PA 19355 Phone: 610.647.8744 Fax: 610.640.4548 Email: sales@semi-gas.com CENTURION-C3-A-1x1x1-082016-V1



## Centurion<sup>™</sup> C3-A

Three Cylinder Fully Automatic Gas Cabinet with 1 x 1 x 1 Enclosure

### SAFETY FEATURES

- Coaxial Tubing for toxic and hazardous gas applications (optional)
- Door Switch Monitor for applications that require extra security and/or limited access (optional)
- UV/IR Detector for pyrophoric gas applications including silane and silane mixtures greater than 1.37% (required for silane)
- Rate of Rise Heat Detector for flammable gas applications (optional)
- Hazardous Gas Detector for all hazardous, toxic, and/or flammable gas applications (required for silane, consult local codes for all other gases)
- Purge Gas Bleed Valve for manifolds and piping systems with large internal volumes or line lengths (optional)

- Controller Z-Purge Kit for systems installed in Class 1 Division 2 hazardous locations, as well as applications for silane and silane mixtures greater than 1.37% (required for silane)
- Dual Cylinder Restraints for applications that require additional cylinder security or are located in seismic zones (required for specific seismic areas)
- ◆ Auto-Guard<sup>™</sup> Cylinder Connection Cover for preventing accidental disconnection of a hazardous gas cylinder from a gas source manifold (optional)
- Shutboy Software Upgrade to accommodate Shutboy valve shutters for automatically closing the gas cylinder valve during emergency situations (optional)

### **ORDERING INFORMATION**

Example: Three Cylinder Fully Automatic Autoswitchover Gas Cabinet with Purge and Individual Process Cabinets



Product

### Configuration



Process Operation Manifold







### Product

C = Centurion<sup>™</sup> Gas Cabinet

### Configuration

- 1 = 1 Cylinder
- 2 = 2 Cylinder
- 3 = 3 Cylinder

#### Control

- M = Manual
- S = Semi Automatic
- A = Fully Automatic

### **Process Manifold**

- 2 = 2-Valve (for inert gases)
- $\mathbf{3} = 3$ -Valve (for inert gases)
- 5 = 5-Valve (for toxic, flammable, and reactive gases)



- X = Autoswitchover
- N = Independent Processes

### Purge

- P = Purge
- O = No Purge

I = Individual Process Cabinets **S** = System Upgrades for Silane

\*All Centurion™ Gas Cabinets can be customized to meet unique specifications. Contact your SEMI-GAS® sales rep for details.





Contact your SEMI-GAS<sup>®</sup> sales rep or visit www.semi-gas.com

### **BY APPLIED ENERGY SYSTEMS**

180 Quaker Lane Malvern, PA 19355 Phone: 610.647.8744 Fax: 610.640.4548 Email: sales@semi-gas.com CENTURION-C3-A-1x1x1-082016-V1

# Option