

# OG Series

ARM Purification offers world class ambient operation purifier technology optimized for a wide range of flow rates.

The OG series purifiers are engineered to remove impurities from **oxygen and oxygenated gases, such as O<sub>2</sub>, CDA, N<sub>2</sub>O, and NO.**



## OG Series Media

Fill Material	Impurities Removed	Outlet Purity	Factory Regenerable	Dangerous Goods	Lifetime of 1 year based on inlet challenge
OG-601	H <sub>2</sub> O	< 100 ppt	yes	no	3 ppm H <sub>2</sub> O
OG-602	H <sub>2</sub> O, CO <sub>2</sub> , NMHC, Acids & Bases, Refractory Compounds	< 100 ppt	yes	no	1 ppm H <sub>2</sub> O
OG-605	Acids & Bases, Refractory Compounds	< 1 ppb	no	no	1 ppm Toluene
OG-606	H <sub>2</sub> O, CO <sub>2</sub> , NMHC	< 100 ppt	yes	no	3 ppm H <sub>2</sub> O
OG-615	NMHC, Refractory Compounds, DMF	< 100 ppt	yes	no	1 ppm NMHC (as Toluene)

## OG Series Size

Model Number	Standard Fitting*	Diameter Inches	Length Inches	Maximum Pressure Rating (psig)	Nominal Flow Rates (slpm)					Max Flow Rates (slpm)
					OG-601	OG-602	OG-605	OG-606	OG-615	
100330	1/4" MVCR (V04)	1.00	3.30	250	0.7	0.7	0.2	0.7	0.8	1
150330	1/4" MVCR (V04)	1.50	3.30	250	1.7	1.8	0.5	1.7	1.9	2
150450	1/4" MVCR (V04)	1.50	4.50	250	3.5	3.7	1.3	3.5	3.9	8.3
150480	1/4" MVCR (V04)	1.50	4.80	250	3.9	4.1	1.4	3.9	4.4	9.4
150500	1/4" MVCR (V04)	1.50	5.00	250	4.2	4.5	1.5	4.2	4.8	10
200630	1/4" MVCR (V04)	2.00	6.30	250	11.4	12.0	3.8	11.4	12.9	30
200820	1/4" MVCR (V04)	2.00	8.20	250	16.7	17.7	6.1	16.7	18.9	45
200880	1/4" MVCR (V04)	2.00	8.80	250	18.3	19.4	7.2	18.3	20.8	49
251250	1/4" MVCR (V04)	2.50	12.50	250	46	49	16	46	52	100
300790	1/2" MVCR (V08)	3.00	7.90	200	35	36	12	35	39	80
300794	1/2" MVCR (V08)	3.00	7.94	200	35	36	11	35	39	80
301000	1/2" MVCR (V08)	3.00	10.00	200	48	50	15	48	54	105
301820	1/2" MVCR (V08)	3.00	18.20	200	102	108	32	102	116	200
401730	1/2" MVCR (V08)	4.00	17.30	200	161	171	60	161	183	500
401760	1/2" MVCR (V08)	4.00	17.60	200	161	171	62	161	183	500
402000	1/2" MVCR (V08)	4.00	20.00	200	193	204	80	193	219	560
403090	1/2" MVCR (V08)	4.00	30.90	200	322	340	100	322	364	600
602760	1/2" MVCR (V08)	6.00	27.60	150	644	681	200	644	729	1000

\*Optional fitting sizes may be available; please consult factory.

The OG series is designed for high and ultra high purity applications that require process gas impurity levels of 100 PPT or less.

**KEY FEATURES**

- 316L stainless filtration media
- 1.5nm outlet filtration
- 316L stainless steel fiber media
- Simple installation
- CE certification available

**OPERATING CONDITIONS**

- Typical operating temperature range of 0°C–50°C (32°F–122°F)
- Max operating temperature of 50°C (122°F)

**ORDERING INFORMATION**

Example: Oxygen/CDA Purifier



**Class**

OG = Oxygen/Oxygenated Gas

**Fill**

See OG Series Media chart for details.

**Size**


First two digits are the diameter (OD); Last four digits are the length (OAL) in inches.

**Fittings**

V04=1/4"      V12=3/4"  
V08=1/2"      V16=1"

**Filtration**

No letter = .1 micron filter  
F = 1.5nm filter



**DON'T SEE WHAT YOU NEED?**

Speak to our team about your requirements and we can work with you to identify the purifier solution best suited for your application.

**Place an Order**

[orders@appliedenergysystems.com](mailto:orders@appliedenergysystems.com)

Contact your ARM Purification sales rep or visit [armpurification.com/request-quote/](http://armpurification.com/request-quote/)



BROUGHT TO YOU BY



[www.appliedenergysystems.com](http://www.appliedenergysystems.com)

180 Quaker Lane  
Malvern, PA 19355 USA  
610.647.8744  
[purification@appliedenergysystems.com](mailto:purification@appliedenergysystems.com)  
[www.armpurification.com](http://www.armpurification.com)  
**ARM-POU-OG-Series-061223-V2**